BUYER'S GUIDE

Specifications & Attachments




Build it Yourself... D-I-Y Kit



MD196K Front Attachments

MANUAL FRONT HITCH KIT - Standard-duty front lifting system. Channel is 3-3/8" tall. Comes complete with dual sets of "lift assist" springs, lift handle and all hardware.





BUCKET MOUTH KIT - Attaches to MD196K-DB44 Dozer Blade with 2 pins! Forms a "mouth" with the Blade and becomes a "clam shell" style bucket. Handles a couple 100 lbs. of dirt, gravel, etc. Dumps with a simple hand lever, not shown.



<u>SPECS</u>

Type As Shipped Engine Brand Engine Size Engine Torque Starting Type Bearing Type Track Clutches Brakes Drawbar Pull Width Length x Height Base Weight Max. Speed Attachment Type

MD RS D-I-Y Kit, Assembled


Unpainted Painted Briggs Honda [250cc] [390cc] 18.5 ft/lbs 11.5 ft/lbs Recoil Electric Standard Heavy-Duty 4 total 6 total Single Dual 1.000 lbs. 1,500 lbs. 41" wide 41" wide 51" x 38" 51" x 38" 575 lbs. 700 lbs. 3.15 MPH 3.15 MPH Hydraulic Manual

MD196K & RS1000 Front Attachments

DOZER BLADE KIT - 42" wide x 15" high x 7GA solid steel, 3 position adjustable blade with replaceable cutting edge. Slotted bolt holes on cutting edge, allow a "slight angle" for driveway maintenance. Angles left and right by moving 1 bolt. Requires Manual or Hydrualic Front Hitch.



BLADE DRAWBAR KIT - Mounts to "top lip" of DB44 Dozer Blade. 9-1/4" wide drawbar with 45° bend. Use for medium-duty pulling. Has 3/4" hole for tow hook or chain clevis. Requires drilling four 5/16" holes in Blade.




RS1000



RS1000 Front Attachments

HYDRO FRONT HITCH KIT - Heavyduty front mounted hitch for easy hydraulic lifting. With "finger-tip" control you can easily move 100's of lbs of soil, manure, sand etc. (Assembled, requires PP35 Power Pack, page 4).



BOX SCRAPER KIT - Attaches to DB44 Dozer Blade to trap and move material. 42" wide x 12+" deep x 18+" high. Hardened and beveled "plow steel" cutting edge. Box scraper shown below mounted to DB44 Dozer Blade.



RS1000 Front Attachments Continued

MATERIAL BUCKET KIT (Manual Dump or Hydro Dump) - Front mounted, heavy-duty, 42-1/2" wide x 12-3/4" high x 13-1/2" deep bucket with hardened cutting edge. 350 lb. rated load. Rear "counterweight" required for maximum loads. Choose BK45 Bucket to Hydraulically dump or BK44 to Manually dump with trip handle shown below.



HITCH EXTENDER KIT - Moves attachment "mounting holes" of Hydro Front Hitch 6" forward. Required for use with D1060UG Backhoe and BK45 Material Bucket Kit.




FRONT WEIGHT KIT - 4" diameter steel weight bar, welded to plates and mounted to the front of RS1000. Necessary for counter-balance of Backhoe. (*Assembled, additional slip on weights available for even more front weight*).

Front Weight

FW15


BUCKET FORKS KIT - Four, 25" long, 19" high, 2-1/2" wide x 1/2" thick solid steel forks quickly mount to BK44 or BK45 Material Bucket with eight locking bolts. 350 lb. rated load. Requires BK44 or BK45 Material Bucket and drilling of holes in "bottom face" of bucket by customer.



MD196K & RS1000 Track Options & More

GROUSER TRACK SHOE KIT -Heavy-duty "U" shaped, 8" wide x 2" deep x 1/2" tall, all-steel shoes, provide the ultimate stiffness and strength to steel track allowing use in rocky

conditions with the best possible traction. Comes complete with all fasteners. Factory assembly available on RS1000. *(Steel tracks only).*



MUD / ICE SCRAPER KIT - Pair of dual "scraper arms" mount between front and rear track sprockets. When tractor is in motion, they continually remove rock chips, mud and snow buildup from between track sprockets. *(Steel tracks only).*



RUBBER TRACK UPGRADE KIT -

Contractor grade rubber tracks, will give you the Power & Traction you need, with the "Velvet Touch" of rubber! Tracks consist of a continuous steel core band and forged steel metal bars inside the rubber. Measures: 7" wide x 72mm pitch x 35 links. *(Assembled on RS1000).*



HOUR METER/TACH KIT - Hour

meter & Tachometer kit gives added

"peace of mind" for scheduled maintenance. Meter is mounted on the front of the dash within easy sight of the operator. (Assembled, for RS1000 only).




Hour/Tach Meter HM10

MD196K Rear Attachments

MANUAL REAR HITCH KIT - Standard-duty "sleeve hitch" rear lifting system. Has 2 "lift-assist" springs to aide in lifting attachments. 2 lbs. of lift handle force will raise 24lb. DR30

> Double Shank Ripper. (Includes basic drawbar shown below).



DOUBLE RIPPER KIT - Two 16" tall x 2" wide x 1/2" deep "hardened steel" ripping teeth mounted to heavy-duty steel channel. Great for loosening



hardpacked driveways and landscaping. Design allows to flip tooth for greater wear.

MANUAL WINCH KIT - Manual utility winch, 800 lb. pull capacity, 5/32" dia.

x 25 ft. long cable with hook. (Requires LW228 Log Crane or mounting location provided by customer).

> Manual Winch LW16

MD196K & RS1000 Rear Attachments

REAR DRAWBAR KIT - Basic pulling on a budget. Drawbar measures: 9-1/4" wide with 90° bend, can be mounted 5-1/2" or 10-1/2" above ground height. Has 3/4" hole for ball hitch. (Cannot be used while any rear attachment is mounted).





HITCH ADAPTER KIT - Class 2 trailer hitch mounts to Rear Hitch with two bolts. Tube ID measures 2", and allows use of dozens of rear attachments, such as: log carriers, garden carts, etc. (Does NOT include ball

hitch).

LCA9

Hitch Adapter MD196K-HA14 **HA14**

LOG CRANE ADAPTER / DRAW-


BAR KIT - Required for use of LW228 Log Crane when a MRH35 or HRH35 Rear Hitch is mounted. Has 3/4" hole for ball hitch. (Can also be used alone when you need a drawbar and have a Rear Hitch mounted).



LOG CRANE KIT - Heavy-duty rear mounted crane. Great for pulling logs on a budget. Add LW16 Manual Winch (at left), or EW20 **Electric Winch** (at right). Has selfcontained drawbar Log Crane with 3/4" MD196K-LW228 LW228 hole for ball hitch.

RS1000 Rear Attachments

HYDRO REAR HITCH KIT - All-hydraulic Rear Hitch allows operator to effortlessly hook-up and move logs, rear-mounted carriers, tillers, compact trailers, etc. (Assembled, requires PP35 Power Pack, pictured on page 4. Includes basic drawbar shown below).



THREE SHANK RIPPER KIT - Three 16" tall x 2" wide x 1/2" deep "hardened steel" ripping teeth mounted to heavy-duty frame. Great for loosening hardpacked driveways and landscaping. Design allows to flip tooth for greater wear.



ELECTRIC WINCH KIT - 12V utility winch, 2,000 lb. pull capacity, 5/32" dia. x 50 ft. long cable with hook. In-

cludes free-spooling clutch release. Operated with push button switches. (Requires LW228 Log Crane or mounting location provided by customer). Electric Winch EW20



Unpainted attachment.

RS1000 Rear Attachments Continued

POWER PACK KIT - Hvdraulic power system for operating hydro attachments. Includes: 3 bank valve, hydraulic oil tank, hoses, breather cap, pump, pulleys, belt & more. (Assembled. See HFH15 Hydro Front Hitch & HRH35 Hydro Rear Hitch).



BACKHOE KIT - 6 1/2" ft. digging depth backhoe, mounts easily to a set of AM39 Angle Mounts Brackets (bottom right), with just a few bolts. D1060UG utilizes (2) hydraulic stabilizers and (2) joystick wobble controls for all digging operations. Comes with fully rotatable and adjustable seat. (Assembled on a secondary pallet).

BACKHOE BUCKET KIT - Standard 12" wide Backhoe Bucket mounts directly to Backhoe dipper arm. Perfect for all around digging use (See below on backhoe). **Backhoe Bucket**

B612

BACKHOE FROST / CHISEL TOOTH RIPPER KIT

- Heavy-Duty single tooth ripper mounts in place of Bucket ... equipped with two types of replaceable teeth, see below:

(#1) 16" tall x 2" wide x 1/2" deep, hardened steel ripping tooth for stone & frost picking & hardpan penetration to 18" (Shown above).

(#2) 17" tall x 1/2" wide x 2" deep, tooth allows root cutting to depths of 18" (Not shown).

Backhoe Frost / Chisel Ripper **BR50**

ROCK / DEBIS THUMB

BACKHOE

D1060UG (Hydraulic

stablizers

not shown)

KIT - Rock "thumb" mounts to Backhoe "dipper arm" of Backhoe with two bolts. Great for grabbing brush. logs and rocks. Distance of Bucket "teeth" to Thumb is adjustable.

SAFETY NOTE: To "safely" counter-balance the Backhoe's weight, FW15, HFH15, at a minimum, the following front attachments should be installed: HE47 and DB44.


FLOAT VALVE UPGRADE KIT - This upgrade allows your hydro front & rear hitch to "float" effortlessly above the ground. Great for backgrading, snow removal or floating a 3rd party rear attachment. (Assembled. Factory upgrade

only). Float Valve Upgrade FVS20

BALLAST BOX KIT - Weight box comes with both mounting brackets to use with the hydro rear hitch or angle mount kit. (For max loads, customer



ROLL-OVER PROTECTIVE STRUC-TURE KIT - The MAGNATRAC'S low center of gravity and ground gripping traction are no substitute for this 80-3/4" tall safety structure. A must if intended to use the MAGNATRAC in a




ANGLE MOUNT KIT - Two heavyduty mounting brackets are the connection point for a ROPS, Backhoe or Ballast Box. (Assembled).

Rock

Гhumb

RT24



Version - 03.10.22